

Code: DS-KD3002-VM

VIDEO DOORPHONE **DS-KD3002-VM** Hikvision



Video Doorphone is mounted in a flush-mounted housing.
The product has been equipped with a network interface, so it can be combined with systems based on the **iVMS-4200** software.

Sensor:	1.0 Mpx CMOS
Display:	3.5 " TFT LCD, 480 x 320 px
Image compression method:	H.264
LED illuminator:	✓
Compatibility:	Hikvision IP Video Doorphones
RS-485:	✓
Ethernet:	10/100/1000 Base-TX
UTP category:	UTP cat. 5e



DATA SHEET

Main features:	<ul style="list-style-type: none">• proximity reader built-in - 13.56 MHz S50, 2500 indexed users,• Wiegand interface,• Keyboard built-in,• LCD display,• Bidirectional communication,• Microphone built-in,• Speakers built-in,• Auto-uploads alarm messages to Master station or once the duress code is entered to open the door,• Auto-uploads captured pictures to FTP or the client,• Tamper detection - removing from mounting surface,• Tamper protections,• Alarm inputs / outputs : 4 / 2,• Port USB 2.0,• Configuration possibility from PC - iVMS-4200 application• Default administrator password : 123456
Operation temp:	-40 °C ... 60 °C
Power supply:	12 V DC / 1.25 A
Power consumption:	≤ 15 W
Housing:	Aluminum
Color:	Silver
Weight:	1.646 kg
Dimensions:	357 x 124 x 59 mm
Supported languages:	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian
Manufacturer / Brand:	Hikvision
SAP Code:	305300697
Guarantee:	3 years