

Code: DS-KIS203

VIDEO DOORPHONE KIT **DS-KIS203** Hikvision

Video Doorphone set of the Hikvision brand with a door station mounted in a surface housing and a 7" colored screen. The DS-KIS203 doesn't need any additional configuration (after connecting according to the diagram the device is ready to operate).
ATTENTION! The device does not support the HIKVISION IP system.



DOOR STATION:	
Sensor:	1/4 " CMOS
IR illuminator:	✓
proximity reader built-in:	—
Video output:	1 Vpp, CVBS - pair of wires compatible with HIKVISION analog video door-phone system
Operation temp:	-30 °C ... 70 °C
Power supply:	12 V DC
Power consumption:	≤ 5 W (operation)
Main features:	<ul style="list-style-type: none"> • Relay output • 4-wire cable installation : 5 m (included)
Housing:	Metal, Waterproof
Color:	Graphite
"Index of Protection":	IP65
Weight:	0.46 kg
Dimensions:	145 x 49 x 27 mm
INDOOR PANEL:	
Shield:	7 " TFT-LCD color matrix
Resolution:	800 x 480

Main features:	<ul style="list-style-type: none">• Plug & Play,• Ultra-flat hands-free monitor, with speakerphone,• Smooth volume control,• Microphone built-in,• Speakers built-in,• Bidirectional communication
Power supply:	12 V DC
Max. current:	420 mA
Power consumption:	≤ 5 W
Operation temp:	-10 °C ... 55 °C
Weight:	0.278 kg
Dimensions:	196 x 133 x 18 mm
Manufacturer / Brand:	Hikvision
SAP Code:	305300749
Guarantee:	3 years