

Code: S601D-2

VIDEO DOORPHONE **S601D-2** VIDOS

Video Doorphone is mounted in a flush-mounted housing. Surface mounting is possible with the D600B3 cover.

Built-in code lock allows to control the opening state of two independent entrances with separate codes (eg wicket + automatic gate).

The S601D-2 is designed to cooperation with video doorphones and panels working in analog VIDOS system.



Compatibility:	VIDOS Analog Video Doorphones
Sensor:	1/3 " 600 TVL
View angle:	87 °
IR illuminator:	✓
LED illuminator:	—
proximity reader built-in:	—
Fingerprint reader built-in:	—
Built-in keypad:	✓
The number of subscribers served:	1
Video output:	compatible with VIDOS analog video door-phone system

Main features:	<ul style="list-style-type: none"> • 2 zones support • Built-in code lock allows to control the opening state of two independent entrances with separate codes (eg wicket + automatic gate) • Possibility to program up to 1010 codes for 2 zones • Adjustment of the opening time of the electric strike: 1s ... 99s • Electric strikes and electromagnetic locks support • Output for the additional lock release button • Timer output specifying temporary access • Possibility of working in bistable mode (entering the code releases the electric strike, re-entering the code closes it) • Vandal-proof front panel • Illuminated buttons and signboard for the surname
Power supply:	12 V DC ... 15 V DC
Power consumption:	≤ 1.5 W (operation)
Housing:	Acid-proof steel / Plastic, Waterproof
Color:	Silver
"Index of Protection":	IP65
Operation temp:	-20 °C ... 55 °C
Weight:	0.66 kg
Dimensions:	195 x 100 x 55 mm
Manufacturer / Brand:	VIDOS
Guarantee:	3 years