

DATA SHEET

Code: S603A-2

VIDEO DOORPHONE **S603A-2** VIDOS

Video Doorphone is mounted in a flush-mounted housing. Surface mounting is possible with the D600B3 cover. Built-in RFID reader allows to control the electric strike using key fobs, proximity cards and tags functioning in the Unique EM 125kHz standard. The S603A-2 is designed to cooperation with video doorphones and panels working in analog VIDOS system.



Compatibility:	VIDOS Analog Video Doorphones
Sensor:	1/3 " 600 TVL
View angle:	87 °
IR illuminator:	✓
LED illuminator:	1
proximity reader built-in:	Standard - Unique EM 125kHz
Fingerprint reader built-in:	1
Built-in keypad:	1
The number of subscribers served:	3
Video output:	compatible with VIDOS analog video door-phone system



DATA SHEET

Main features:	2 zones support Number of supported proximity cards: max. 1010 Adjustment of the opening time of the electric strike: 1s 99s Electric strikes and electromagnetic locks support Output for the additional lock release button Possibility of working in bistable mode (close-up of the card releases the electric strike, re-closing closes it) Vandal-proof front panel Illuminated buttons and signboards for the surnames
Power supply:	12 V DC 15 V DC
Power consumption:	≤ 1.5 W (operation)
Housing:	Acid-proof steel / Plastic, Waterproof
Color:	Silver
"Index of Protection":	IP65
Operation temp:	-20 °C 55 °C
Weight:	0.86 kg
Dimensions:	280 x 100 x 55 mm
Manufacturer / Brand:	VIDOS
Guarantee:	3 years