

Code: S1101A

VIDEO DOORPHONE **S1101A** VIDOS

Video Doorphone is mounted in a surface housing. The S1101A is dedicated for cooperation with video doorphones and panels compatible with the VIDOS DUO digital system.



Compatibility:	VIDOS DUO
Sensor:	1/2.7 ", 600 TVL
View angle:	105 °
IR illuminator:	—
LED illuminator:	✓
proximity reader built-in:	Standard : Unique EM 125kHz
The number of subscribers served:	1
Video output:	compatible with the VIDOS DUO digital video doorphone system
Main features:	• Wiring - 2 wires without polarity • Relay output : 1 pcs or 2 pcs - B5 module • Support up to 12 indoor devices (monitors / uniphones) • PIR detectors support • Permanent or cyclical zoom-up of the observed image • Electric strikes and electromagnetic locks support • Electric lock supply: 12V DC / max. 300mA • Easy to add and delete users via MASTER key fobs • Call start and lock opening indicator
Power supply:	24 V DC



DATA SHEET

Power consumption:	≤ 3 W (operation) ≤ 0.8 W (Standby mode)
Housing:	Metal, Waterproof
Color:	Silver
"Index of Protection":	IP54
Operation temp:	-20 °C ... 55 °C
Weight:	0.62 kg
Dimensions:	180 x 95 x 42 mm
Manufacturer / Brand:	VIDOS
Guarantee:	3 years

