

Code: S1401D

VIDEO DOORPHONE **S1401D** VIDOS

Video Doorphone is mounted in a flush-mounted housing. The S1401D is dedicated for cooperation with video doorphones and panels compatible with the VIDOS DUO digital system.



Compatibility:	VIDOS DUO
Sensor:	1/2.7", 2.0 Mpx
View angle:	170 °
IR illuminator:	—
LED illuminator:	✓
Fingerprint reader built-in:	—
proximity reader built-in:	—
Built-in keypad:	✓
The number of subscribers served:	1
Video output:	compatible with the VIDOS DUO digital video doorphone system

Main features:	<ul style="list-style-type: none"> • Fisheye lens • Wiring - 2 wires without polarity • Relay output : 1 pcs or 2 pcs - B5 Module • Support up to 12 indoor devices (monitors / uniphones) • Touch control keys • Illuminated buttons and signboard for the surname • PIR detectors support • Permanent or cyclical zoom-up of the observed image • Electric strikes and electromagnetic locks support • Electric lock supply: 12V DC / max. 300mA • Call start and lock opening indicator
Power supply:	24 V DC
Power consumption:	<ul style="list-style-type: none"> ≤ 3 W (operation) ≤ 0.8 W (Standby mode)
Housing:	Acid-proof steel, Waterproof
Color:	Silver
"Index of Protection":	IP54
Operation temp:	-18 °C ... 55 °C
Weight:	0.7 kg
Dimensions:	220 x 120 x 50 mm
Manufacturer / Brand:	VIDOS
Guarantee:	3 years

