

Code: S1204A

VIDEO DOORPHONE **S1204A** VIDOS

Video Doorphone is mounted in a flush-mounted housing. The S1204A is dedicated for cooperation with video doorphones and panels compatible with the VIDOS DUO digital system.



Compatibility:	VIDOS DUO
Sensor:	1/2.7 " Fish Eye CMOS, 2 Mpx
View angle:	170 °
IR illuminator:	—
LED illuminator:	✓
proximity reader built-in:	Standard : Unique EM 125kHz
The number of subscribers served:	4
Video output:	compatible with the VIDOS DUO digital video doorphone system
Main features:	<ul style="list-style-type: none"> • Wiring - 2 wires without polarity • Relay output : 1 pcs or 2 pcs - B5 Module • Support up to 12 internal devices - 4 for each premises • PIR detectors support • Permanent or cyclical zoom-up of the observed image • Electric strikes and electromagnetic locks support • Electric lock supply: 12V DC / max. 300mA • Easy to add and delete users via MASTER key fobs
Power supply:	24 V DC



DATA SHEET

Power consumption:	≤ 3 W (operation) ≤ 0.8 W (Standby mode)
Housing:	Acid-proof steel / Plastic, Waterproof
Color:	Silver
"Index of Protection":	IP54
Operation temp:	-20 °C ... 55 °C
Weight:	0.72 kg
Dimensions:	220 x 120 x 49 mm
Manufacturer / Brand:	VIDOS
Guarantee:	3 years