

Code: ASC1204C-D

ACCESS CONTROLLER **ASC1204C-D** DAHUA

The ASC1204C-D controller is intended to use in access control systems based on electrical control of door opening.



Number of served transitions:	4 (two-way)
Support:	DAHUA
Number of supported readers:	8 pcs
Battery backup support:	max. 7 Ah
Input lines:	20 pcs
Output lines:	12 pcs - Relay
Communication:	<ul style="list-style-type: none">• RS-485,• Ethernet,• Wiegand 34/26
Power supply:	85 ... 264 V AC



DATA SHEET

Main features:	<ul style="list-style-type: none">• Support for 4 doors (20 inputs: 4x lock state, 4x door sensor, 4x exit button, 8x alarm line)• 100000 indexed users• History of 150000 events• 128 General Purpose Schedules• Function to prevent of multiple use of the same code/card to gain access (anti-passback)• Door Left Open and Door Forced Open alarms• Tamper detection - opening the enclosure• Watchdog built-in• Remote programming from PC• Metal housing
Operation temp:	-30 °C ... 60 °C
Permissible relative humidity:	max. 95 % (non-condensing)
Weight:	2.63 kg
Dimensions:	280 x 320 x 115 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years