

Code: APTI-2STC6-40P

IP CAMERA **APTI-2STC6-40P** - 1080p 6 mm

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

Camera bracket allows to adjust the camera to any direction, and power cables are hidden inside the bracket. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Thanks to the "Starlight" technology used, the camera only needs very low lighting to obtain a clear color image.



Standard:	TCP/IP
Sensor:	1/2.8 " Sony CMOS IMX290 STARVIS Back-illuminated
Digital Image Processor:	Hisilicon 3516C
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	6 mm, 3 Mpx
View angle:	<ul style="list-style-type: none"> • 46 ° (manufacturer data) • 55 ° (our tests result)
S/N ratio:	≥ 52 dB
Range of IR illumination:	60 m
IR illuminator power adjustment:	Automatic
Image compression method:	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Bitrate:	64 ... 15000 kbps
Main stream frame rate:	25 fps @ 1080p
Network interface:	10/100 Base-T (RJ-45)
Alarm inputs / outputs:	—



DATA SHEET

Audio:	External microphone input
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
WEB Server:	Built-in - port 80
Max. number of on-line users:	10
ONVIF:	2.4
RS-485 interface:	—
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application FREEIP• iOS (iPhone): Free application FREEIP
Default IP address:	192.168.1.168
Default admin user / password:	admin / admin
Web browser access ports:	80
PC client access ports:	80
Mobile client access ports:	80
Port ONVIF:	80
RTSP URL:	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Main features:	<ul style="list-style-type: none">• WDR - Wide Dynamic Range• 2D-DNR, 3D-DNR - Digital Noise Reduction• F-DNR (Defog) - Reduction of image noise caused by precipitation• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect• ICR - Movable InfraRed filter• BLC - Back Light Compensation• Possibility to change the resolution, quality and bit rate• Motion Detection• Privacy zones• Mirror - Mirror image• Day/Night mode - configurable• RESET button - on the cable
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 620 mA
Power consumption:	≤ 7.5 W
Housing:	Compact, Aluminum
Color:	White / Black
"Index of Protection":	IP66
Operation temp:	-20 °C ... 60 °C
Weight:	1.13 kg
Dimensions:	310 x 108 x 101 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian



DATA SHEET

Manufacturer / Brand:	APTI
Guarantee:	2 years

