

Code: S1108A

VIDEO DOORPHONE **S1108A** VIDOS



Video Doorphone is mounted in a surface housing. The S1108A is dedicated for cooperation with video doorphones and panels compatible with the VIDOS DUO digital system.

Compatibility:	VIDOS DUO
Sensor:	1/2.7 " Fish Eye CMOS, 2 Mpx
View angle:	170 °
IR illuminator:	—
LED illuminator:	✓
proximity reader built-in:	Standard : Unique EM 125kHz
Built-in keypad:	—
The number of subscribers served:	8
Video output:	compatible with the VIDOS DUO digital video doorphone system
Main features:	• Wiring - 2 wires without polarity • Relay output : 1 pcs or 2 pcs - B5 module • Permanent or cyclical zoom-up of the observed image • Electric strikes and electromagnetic locks support • Electric lock supply: 12V DC / max. 300mA • Easy to add and delete users via MASTER key fobs • Call start and lock opening indicator • Built-in information signboard module with backlight



DATA SHEET

Power supply:	24 V DC
Power consumption:	≤ 4.8 W (operation) ≤ 1.2 W (Standby mode)
Housing:	Acid-proof steel / Plastic, Waterproof
Color:	Silver
"Index of Protection":	IP54
Operation temp:	-20 °C ... 55 °C
Weight:	0.98 kg
Dimensions:	281 x 110 x 44 mm
Manufacturer / Brand:	VIDOS
Guarantee:	3 years

