

Code: DS-7332HGHI-SH

## HD-TVI, TCP/IP, PAL DVR **DS-7332HGHI-SH** 32 CHANNELS +eSATA Hikvision

The DS-7332HGHI-SH digital recorder with HD-TVI (High Definition Transport Video Interface), IP - Hikvision and PAL interface is a professional device applicable in surveillance systems.

The HD-TVI interface allows to transmission of analog video signal via coaxial cable at resolutions up to 1080p. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



Standard:	HD-TVI, TCP/IP, PAL
Video inputs:	32 pcs BNC - HD-TVI / CVBS
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	4 pcs CINCH 1 pcs LINE IN - CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	Adjustable bitrate 32 ... 6144 kbps
Image records resolutions:	<ul style="list-style-type: none"> <li>• HD-TVI : 1080p - 1920 x 1080 720p - 1280 x 720 VGA - 640 x 480</li> <li>• CVBS : 960 x 576 - 960H 704 x 576 - D1</li> <li>• IP : max. 1080p - 1920 x 1080</li> </ul>
Recording speed adjustment:	1080p IP @ 1 ... 25 fps 1080p @ 1 ... 12 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps D1 @ 1 ... 25 fps for each channel
Operation modes:	32 x HD-TVI / CVBS / IP + 8 x IP ( max. 32 x IP )
Recording modes:	Manual, Sensor, Motion detection, Schedule
Supported hard drives:	4 x 6 TB SATA + Port eSATA



# DATA SHEET

External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast, slow.
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols:	TCP/IP, PPPoE, DHCP, Hik Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP, HTTPS
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) Android: Free application <a href="#">iVMS-4500</a> iOS (iPhone): Free application <a href="#">iVMS-4500</a>
Default IP address:	192.0.0.64
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80
PC client access ports:	8000
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	<ul style="list-style-type: none"><li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li><li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li></ul>
Alarm inputs / outputs:	16 / 4
PTZ control:	RS-485 - PELCO-D/P Control compatible with coax HD-TVI Hikvision
Motion Detection:	Split the screen into zones 22 x 18 motion zones
USB:	3 pcs USB 2.0
Mouse support:	✓
IR remote controller in the set:	✓
Power supply:	230 V AC
Color:	Black
Weight:	5.4 kg
Dimensions:	440 x 407 x 75 mm Rack 19", 1.5 U
Supported languages:	English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, German, Norwegian, Polish, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	300214430
Country of origin:	China
Guarantee:	<b>3 years</b>