

Code: DSA-64

## Switch PoE 6-PORT **DSA-64** PULSAR

DSA-64 is designed to mount on the DIN 35 mm rail. PoE/PoE+ powering possibility, compatible with the 802.3af/at standard makes the device more universal and easier to install. Switch has built-in a 52 V DC power supply adapter with power of 48 W.



LAN ports:	<ul style="list-style-type: none"> <li>• 6 x RJ45 ( 4 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 - Uplink</li> </ul>
Management:	—
Transmission method:	Store and Forward
LED diodes:	Power, PoE, Link/Act
Transmission speed:	10 / 100 Mbps - 6 x LAN & PoE ports
Maximal output power:	30 W / port PoE+
Maximal total power:	48 W
MAC addresses table:	1k - Auto update of MAC addresses table
Main features:	<ul style="list-style-type: none"> <li>• DIN, TS-35 rail mounting,</li> <li>• Switch has built-in a 52 V DC power supply adapter with power of 48 W</li> <li>• Auto-learning and Auto-aging functions support for MAC addresses</li> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Short-circuit protection</li> <li>• Overload protection</li> </ul>
Power supply:	176 V ... 264 V AC
Housing:	Steel - powder painted
Color:	Black (RAL 9005)
Weight:	1.8 kg
Dimensions:	190 x 130 x 90 mm



# DATA SHEET

---

Manufacturer / Brand:	PULSAR
Guarantee:	2 years