

Code: DSB-64

## POE SWITCH WITH BATTERY BACKUP **DSB-64** 6-PORT PULSAR

The DSB-64 is 6-port PoE switch with battery backup designed to power IP cameras operating in IEEE 802.3af/at standard.

With the built-in buffered power supply adapter it can operate with two 12V / 17Ah batteries connected in series and in case of power failure, immediate switching to battery supply. DSB-64 is designed to mount on the DIN 35 mm rail.

Caution! A battery is not included with the switch. The value of 15.4 W per port is the maximal one. With full occupation of PoE ports the total power consumption should not exceed 48 W.



LAN ports:	<ul style="list-style-type: none"> <li>• 4 x RJ45 - PoE (802.3af/at),</li> <li>• 2 x RJ45 - Uplink</li> </ul>
Port Uplink:	2 x RJ45
Transmission method:	Store and Forward
LED diodes:	Power, PoE, Link/Act
Transmission speed:	10 / 100 Mbps - 4 x LAN & PoE ports
Maximal output power:	30 W / port PoE
Maximal total power:	48 W
MAC addresses table:	1k - Auto update of MAC addresses table
Main features:	<ul style="list-style-type: none"> <li>• DIN, TS-35 rail mounting,</li> <li>• Built-in buffered power supply working with one 7Ah / 12V or 17Ah / 12V battery,</li> <li>• Built-in converter increasing the voltage to 52V DC (PoE switch power supply)</li> </ul>
Power supply:	176 V ... 264 V AC
Housing:	Steel - powder painted
Color:	Black (RAL 9005)
Weight:	2.66 kg
Dimensions:	250 x 166 x 110 mm



# DATA SHEET

---

Manufacturer / Brand:	PULSAR
Guarantee:	2 years