

Code: VMT-194

## MONITOR HDMI, VGA, CVBS **VMT-194** 19.5 " VILUX



Monitor is equipped with plastic housing.

The LED matrix illumination technology allows to real colors reproduction, 40% lower current consumption and much lower failure rate compared to normal LCD monitors with CCFL illumination. It has two types of mounting. As standalone or VESA 100 mounting.

This model is equipped with all kinds of inputs, what allows to display an image from any kind of signals using in CCTV systems.

Monitor is designed to the display of advertising spots from computer in public places such as waiting rooms, etc. Very interesting solution is placing the speakers of the back side of housing. It does not bother listening to the AUDIO from the recorder at the same time does not reduce the area of the monitor front panel.

The device is designed to continuous work in closed spaces.

|                      |                                    |
|----------------------|------------------------------------|
| Screen size:         | 19.5 "                             |
| Native resolution:   | 1920 x 1080 px                     |
| Aspect ratios:       | 16 : 9                             |
| Matrix type:         | TFT-LCD color matrix               |
| Matrix backlight:    | In LED technology                  |
| Supported standards: | PAL/NTSC                           |
| Contrast:            | 3000 : 1                           |
| Brightness:          | 700 cd/m <sup>2</sup>              |
| Viewable angles:     | 170 ° horizontal<br>170 ° vertical |
| Response time:       | 5 ms                               |
| Speakers built-in:   | 2 x 2.5 W                          |



# DATA SHEET

|                            |   |
|----------------------------|---|
| Signal connectors:         | Composite Video (BNC) sockets: 1x in, 1x out<br>1x VGA<br>1x HDMI<br>Audio: 1x Jack (for VGA) |
| Housing type:              | Plastic   |
| Monitor mounting standard: | VESA 100  |
| Power supply:              | 12 V DC / 3 A (power adapter included)  |
| Power consumption:         | max. 25 W   |
| Monitor control:           | OSD - by IR remote controller or monitor control keys   |
| Main features:             | 3D Comb Filter  |
| Weight:                    | 2.66 kg   |
| Dimensions:                | 486 x 374 x 190 mm (with stand)<br>486 x 300 x 52 (without stand)                             |
| Supported languages:       | English, Chinese, French, German, Italian   |
| Manufacturer / Brand:      | VILUX   |
| Guarantee:                 | 2 years   |