

Code: DS-2CE38D8T-PIR(2.8MM)

HD-TVI CAMERA **DS-2CE38D8T-PIR(2.8MM)** - 1080p Hikvision

Megapixel camera with Progressive scan CMOS sensor and HD-TVI. The HD-TVI interface allows to transmission of analog video signal via coaxial cable at resolutions up to 1080p. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image. In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.



Standard:	HD-TVI
Sensor:	Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Range of IR illumination:	20 m
IR illuminator power adjustment:	Automatic
Lens:	2.8 mm
View angle:	103 °
S/N ratio:	> 65 dB
Video output:	1 x HD-TVI - BNC socket
Audio:	<ul style="list-style-type: none"> • Microphone built-in • Audio output - Cinch socket
OSD menu:	✓

Main features:	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC - Back Light Compensation • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Mirror - Mirror image • Auto White Balance • PIR detector - Built-in, Range : 11 m, Detection angle : 110 °
Power supply:	12 V DC / 420 mA
Power consumption:	≤ 5 W
Housing:	Plastic
Color:	White
"Index of Protection":	—
Operation temp:	-40 °C ... 60 °C
Weight:	0.208 kg
Dimensions:	131 x 73 x 90 mm (with stand)
Manufacturer / Brand:	Hikvision
SAP Code:	300509666
Guarantee:	3 years