

Code: ASI1212A(V2)

ACCESS CONTROLLER **ASI1212A(V2)** DAHUA

The ASI1212A(V2) controller can operate autonomously or in the network mode. The device enables single door or read in/out access control. In case of read in/out access control the controller must be connected to the external access reader of the ASR series or to the reader equipped with the Wiegand interface.

To add a device in Smart PSS please enter the data: User: admin, Password: 123456.



Cards support:	13.56 MHz S50
Reading distance of prox-keys:	max. 8 cm
Keyboard built-in:	Touch control keys
Autonomous operation:	✓
Battery backup support:	—
Input lines:	3
Output lines:	4
Identification time:	< 1.5 s
FAR (False Acceptance Rate):	< 0.00004 %
FRR (False Rejection Rate):	< 0.15 %
Communication:	<ul style="list-style-type: none"> • RS-485 • Wiegand • LAN
Network interface:	10/100 Base-T
Default admin user / password:	- / 88888888
Power supply:	10 ... 15 V DC





DATA SHEET

Main features:	<ul style="list-style-type: none">• 13.56 MHz S50 proximity reader built-in,• Fingerprint reader built-in• Memory of 3000 fingerprint patterns• Possible connection of the external ASR series reader (read in/out door control)• Identification modes : PIN, Proximity identifier 13.56 MHz S50, Fingerprint, Any combination of the above• Tamper detection - removing from mounting surface• Support for door contact and exit button• Indication of forced entry and the lack of closing doors• 30000 indexed users• 6 access groups• 128 General Purpose Schedules• 128 time periods within single Schedule• Holiday Schedules• Anti-passback• History of 150000 events• Integration with an alarm system via in/out line• Remote programming from PC• Watchdog built-in
Operation temp:	-30 °C ... 60 °C
Permissible relative humidity:	max. 95 % (non-condensing)
Weight:	0.39 kg
Dimensions:	193 x 161 x 33 mm
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years