

Code: VTO6210B

VIDEO DOORPHONE **VTO6210B** DAHUA

The device works with video doorphones, and other DAHUA panels. Video Doorphone is mounted in a surface housing.

ATTENTION! The device does not support the Dahua analogue system.



Sensor:	1/4 ", 1.0 Mpx CMOS
Image compression method:	H.264
LED illuminator:	✓
Compatibility:	DAHUA
proximity reader built-in:	Access control cards - 13.56 MHz S50
UTP category:	UTP cat. 5e
Main features:	• Doorbell button, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS There are also other versions of mobile applications: gDMSS Plus, iDMSS Plus
Power supply:	• 12 V DC / 830 mA, • 24 V PoE - DAHUA
Housing:	Plastic / Tempered glass, Waterproof



DATA SHEET

"Index of Protection":	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone
Color:	Black
Operation temp:	-30 °C ... 60 °C
Weight:	0.37 kg
Dimensions:	154 x 114 x 43 mm
Supported languages:	English, Bulgarian, Czech, Finnish, Polish, Slovenian, Slovak, Hungarian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

