

Code: NVR2104-4KS2

## NVR **NVR2104-4KS2** 4 CHANNELS, 4K UHD DAHUA



|                                  |                                                                                                             |
|----------------------------------|-------------------------------------------------------------------------------------------------------------|
| Standard:                        | TCP/IP                                                                                                      |
| Supported resolutions:           | max. 8.3 Mpx - 3840 x 2160 px, 4K UHD                                                                       |
| Video outputs:                   | 1 pcs HDMI<br>1 pcs VGA                                                                                     |
| Audio support:                   | 4 Channels - Audio from cameras                                                                             |
| Audio inputs:                    | 1 pcs CINCH                                                                                                 |
| Audio outputs:                   | 1 pcs CINCH                                                                                                 |
| Image compression method:        | H.265, H.264                                                                                                |
| Supported hard drives:           | 1 x 6 TB SATA                                                                                               |
| Recording modes:                 | Manual, Motion Detection, Schedule                                                                          |
| Network protocols:               | HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, NTP, DHCP, DNS, DDNS, IP Filter, FTP, IP Search, ONVIF 2.4 |
| External storage devices backup: | Backup to USB drive (pendrive, external drive)                                                              |
| Default admin user / password:   | admin / admin                                                                                               |
| Default IP address:              | 192.168.1.108                                                                                               |
| Web browser access ports:        | 80, 37777                                                                                                   |
| PC client access ports:          | 37777                                                                                                       |
| Mobile client access ports:      | 37777                                                                                                       |



# DATA SHEET

|                                     |                                                                                                                                                                                                                                                                  |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RTSP URL:                           | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream                                                                                  |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>All channels synchronous playback, Smart Search function                                                       |
| Bitrate:                            | max. 80 Mbps                                                                                                                                                                                                                                                     |
| Network functions:                  | Full support via network, Remote records copying, Web Server built-in<br>max. 128 on-line users                                                                                                                                                                  |
| Mobile phones support:              | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application <a href="#">DMSS</a><br>• iOS (iPhone): Free application <a href="#">DMSS</a><br><br>See how to configure the P2P function in Dahua recorders and how to enable the mobile application |
| Alarm inputs / outputs:             | —                                                                                                                                                                                                                                                                |
| PTZ control:                        | IP Speed Dome Cameras                                                                                                                                                                                                                                            |
| Motion Detection:                   | 22 x 18 motion zones - after motion detection records detected channels only                                                                                                                                                                                     |
| USB:                                | 2 pcs USB 2.0                                                                                                                                                                                                                                                    |
| Mouse support:                      | ✓                                                                                                                                                                                                                                                                |
| IR remote controller in the set:    | —                                                                                                                                                                                                                                                                |
| Power supply:                       | 12 V DC / 2 A (power adapter included)                                                                                                                                                                                                                           |
| Weight:                             | 0.43 kg                                                                                                                                                                                                                                                          |
| Dimensions:                         | 205 x 205 x 48 mm                                                                                                                                                                                                                                                |
| Supported languages:                | English, Bulgarian, Czech, Finnish, Greek, Polish, Romanian, Serbian, Slovenian, Hungarian                                                                                                                                                                       |
| Country of origin:                  | China                                                                                                                                                                                                                                                            |
| Manufacturer / Brand:               | DAHUA                                                                                                                                                                                                                                                            |
| Guarantee:                          | <b>3 years</b>                                                                                                                                                                                                                                                   |