

Code: PFWB5-90AC

CUSTOMER PREMISES EQUIPMENT **PFWB5-90AC** DAHUA



The PFWB5-90AC is an integrated solution for professional outdoor wireless networks.

The casing made of UV resistant plastic is resistant to even the most severe weather conditions.

| | |
|------------------------------|--|
| Frequency range: | 5150 MHz ... 5850 MHz |
| Antenna type: | 18 dBi, 2x2 MIMO - Bandwidth 5 GHz |
| Standards: | IEEE 802.11 a/n/ac |
| Baud rates: | max. 866 Mbps |
| LAN ports: | 1 x 10/100/1000 Mbps |
| Vertical beam width (V): | 20 ° |
| Horizontal beam width (H): | 90 ° |
| Operation modes: | WDS client, TDMA client, WDS Base Station, TDMA Base Station, ARP NAT Base Station, Bridge, Router |
| Protections: | Overvoltage protection |
| Transmitter power: | 30 dBm |
| Wireless transmission range: | <ul style="list-style-type: none">• Recommended ≤ 5 km• max. 7 km |
| Memory: | 64 MB RAM, 16 MB Flash |



DATA SHEET

| | |
|-----------------------|---|
| Processor: | QCA9563 750 MHz |
| Power supply PoE: | ✓ |
| Power supply: | 12 V ... 24 V DC - Passive PoE (power adapter included) |
| Power consumption: | 10 W |
| Operation temp: | -30 °C ... 70 °C |
| Weight: | 0.57 kg |
| Dimensions: | 383 x 100 x 98 mm |
| Manufacturer / Brand: | DAHUA |
| Guarantee: | 3 years |

