

Code: ACCO-KPWG

DOOR CONTROLLER **ACCO-KPWG** SATEL

The ACCO-KPWG controller is designed for control of a single door within the ACCO/ACCO NET access control systems. Users authorization is based on code or passive transponder (proximity card, tag, etc.). The device is provided with a relay output that can be used to operate electromagnetic lock or another door activating device. Owing to additional inputs and outputs, the module can work in conjunction with the alarm system.

The ACCO-KPWG controller can operate autonomously or in the network mode.



Input lines:	5
Output lines:	2
Operation modes:	• Autonomous operation, • Work in the ACCO/ACCO NET system
Current-carrying capacity of OC output:	50 mA
Relay switching voltage:	250 V AC
Relay contacts load:	8 A
Communication:	RS-485, RS-232
Main features:	• Support for single door with entry and exit authorization • 1024 users • Possibility to add different privileges to the users • Identification: Card and/or PIN • History of 24 576 events • Recording of information about Time&Attendance • 256 General Purpose Schedules • Holiday access schedules • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Limiting of accesses



DATA SHEET

Power supply:	12 V DC / 110 mA (max)
Battery backup support:	—
Permissible relative humidity:	95 %
Operation temp:	-10 °C ... 55 °C
Weight:	0.23 kg
Dimensions:	• 126 x 159 x 31 mm - Housing • 74 x 104 mm - PCB
Manufacturer / Brand:	SATEL
Guarantee:	2 years