

Code: SLIM-PIR-LUNA

## PIR DETECTOR **SLIM-PIR-LUNA** SATEL

Digital passive infrared detector with LED lighting function.



|                                   |                                               |
|-----------------------------------|-----------------------------------------------|
| Application:                      | Indoor                                        |
| Pyroelectric sensor:              | Double                                        |
| Sensor type:                      | Passive Infra Red (PIR)                       |
| Range:                            | 20 x 24 m, 90 °                               |
| Sensitivity adjustment:           | Possibility to set 1 of 16 sensitivity levels |
| Pet immunity:                     | —                                             |
| Alarm time:                       | 2 s                                           |
| Maximal outputs load:             | 40 mA / 24 V DC                               |
| Digital temperature compensation: | ✓                                             |
| Target speed range:               | 0.3 ... 3 m/s                                 |
| Power supply:                     | 12 V DC / 97 mA (max)                         |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:        | <ul style="list-style-type: none"><li>• Lighting function implemented by means of LED diodes</li><li>• Compliance to EN 50131-2-2 @ Grade 2 standard</li><li>• Optical tamper protection which reacts to opening the housing and pulling away from the wall</li><li>• Remote on/off of the LED indicator and choice of lighting color from 7 colors</li><li>• Built-in parametric resistors 2EOL: 2 x 1.1kΩ, 2 x 4.7 kΩ, 2 x 5.6 kΩ</li><li>• Remote controlled (not included)</li></ul> |
| Operation temp:       | -10 °C ... 55 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Weight:               | 0.11 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Dimensions:           | 62 x 137 x 42 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Manufacturer / Brand: | SATEL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Guarantee:            | <b>5 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |