

Code: APTI-H50V2-28W

## AHD, HD-CVI, HD-TVI CAMERA **APTI-H50V2-28W** 2Mpx / 5Mpx 2.8 mm

Megapixel camera with 1/2.7" CMOS sensor and AHD / HD-CVI / HD-TVI.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.

The appropriate signal format selection is done by tilting and holding the joystick for 5 s without entering to the OSD menu. Changing the signal to the NTSC in the camera causes loss of image in connected AHD/HD-CVI/HD-TVI recorder.

**Attention!** The camera is factory set to the resolution 2 Mpx (1080p).



Standard:	AHD, HD-CVI, HD-TVI
Sensor:	1/2.7 " Progressive Scan CMOS
Matrix size:	5 Mpx
Resolution:	<ul style="list-style-type: none"> <li>• 2592 x 1944 - 5 Mpx - AHD / HD-TVI,</li> <li>• 2560 z 1440 - 3.7 Mpx @ AHD / HD-CVI / HD-TVI,</li> <li>• 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI</li> </ul>
Range of IR illumination:	20 m
IR illuminator power adjustment:	Automatic
Lens:	2.8 mm
View angle:	<ul style="list-style-type: none"> <li>• 95 ° (manufacturer data)</li> <li>• 99 ° (our tests result)</li> </ul>
Video output:	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch
OSD menu:	✓

Main features:	<ul style="list-style-type: none"><li>• DNR - Digital Noise Reduction</li><li>• D-WDR - Wide Dynamic Range</li><li>• ICR - Movable InfraRed filter</li><li>• AGC - Automatic Gain Control</li><li>• BLC - Back Light Compensation</li><li>• Day/Night mode (color/b&amp;w/auto)</li><li>• White Balance - ATW/Manual</li><li>• Sharpness - sharper image outlines</li></ul>
Power supply:	12 V DC / 310 mA
Power consumption:	≤ 3.7 W
Housing:	Dome - Metal
Color:	White
"Index of Protection":	IP66
Vandal-proof:	✓
Supported languages:	English, Portuguese, Russian, Italian
Manufacturer / Brand:	APTI
Operation temp:	-20 °C ... 60 °C
Weight:	0.28 kg
Dimensions:	Ø 93 x 77 mm
Guarantee:	2 years