

Code: APTI-RF08/N0901-S3

NVR **APTI-RF08/N0901-S3** Wi-Fi, 9 CHANNELS

The APTI-RF08/N0901-S3 digital recorder is a professional device applicable in surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easily navigate and change parameters in DVR settings without any problem.

The Wi-Fi module used in the device allows the device to operate also in places with limited wiring possibilities.

Attention! In order for the Wi-Fi cameras to search for and connect to the recorder, you should change the default network settings: Menu->Configuration->Network->Wi-Fi->Advanced: SSID broadcast - enable ; Wi-Fi Channel: 1 ; Area: EU.



Standard:	TCP/IP
Supported resolutions:	max. 5 Mpx - 2592 x 1944
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio support:	9 Channels - Audio from cameras
Audio inputs:	—
Audio outputs:	1 pcs Jack 3.5 mm socket
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Supported hard drives:	1 x 8 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
Network protocols:	ONVIF, Private
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast Channels played simultaneously : 4 @ 1080p or 1 @ 5 Mpx
Bitrate:	60 Mbps



DATA SHEET

Network functions:	<ul style="list-style-type: none">• Support up to 9 TCP/IP cameras including to 8 Wi-Fi cameras,• Wi-Fi - 2.4 GHz, APTI cameras support, Range : 50 m (open area)• Client application: live view, playback and backup of the records; IE browser: live view, playback and backup of the records, configuration of the recorder parameters
ONVIF:	✓
Mobile phones support:	Port no.: 6000 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application BitVision• Android: Free application iVMS320• iOS (iPhone): Free application BitVision• iOS: Free application iVMS320
Default admin user / password:	admin / 12345
Default IP address:	192.168.1.168
Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554
Mobile client access ports:	80, 5000, 554
Alarm inputs / outputs:	—
PTZ control:	—
Motion Detection:	Split the screen into zones : 24 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A
Operation temp:	-10 °C ... 55 °C
Weight:	0.7 kg
Dimensions:	260 x 220 x 45 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Spanish, German, Portuguese, Russian, Turkish, Hungarian, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years

