

Code: PFT1310

## POE SWITCH / EXTENDER **PFT1310** 3-PORT

The PFT1310 device allows for connection of 2 cameras with PoE power supply using a single Ethernet line. The cascading connection of 2 extenders allows to connect up to 3 cameras in this way. The device is powered from the PoE switch or other device compliant with this standard. Thanks to this, neither the extender nor the camera connected to it require any additional power supply.



|                       |                                                                                                                                                                     |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAN ports:            | <ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at),</li> <li>• 2 x RJ45 10/100 Base-T + PoE (802.3af)</li> </ul>      |
| Management:           | —                                                                                                                                                                   |
| LED diodes:           | LAN, PoE                                                                                                                                                            |
| Transmission speed:   | 10 / 100 Mbps                                                                                                                                                       |
| Maximal output power: | <ul style="list-style-type: none"> <li>• 15.4 W @ port PoE - First device</li> <li>• 3 W @ port PoE - Second device in cascade</li> </ul>                           |
| Main features:        | <ul style="list-style-type: none"> <li>• Possibility to connecting in cascade</li> <li>• The device can function as a LAN network and PoE power extender</li> </ul> |
| Power consumption:    | 0.3 W                                                                                                                                                               |
| Range:                | 100 m - Input<br>100 m - Output                                                                                                                                     |
| Protections:          | Overvoltage                                                                                                                                                         |
| Housing:              | Plastic, DIN, TS-35 rail mounting                                                                                                                                   |
| Power supply:         | PoE (802.3af/at)                                                                                                                                                    |



## DATA SHEET

|                                      |                             |
|--------------------------------------|-----------------------------|
| Operation temp. / Relative humidity: | -30 ... 65 °C / 10 ... 90 % |
| Weight:                              | 0.05 kg                     |
| Dimensions:                          | 79 x 52 x 23 mm             |
| Guarantee:                           | 2 years                     |