



DATA SHEET

Code: UT-132B

UNIVERSAL METER **UT-132B** UNI-T



UT-132B is a universal digital meter used to measure: voltage, current, resistance. The device also has a built-in battery tester.

| | |
|--------------------------|--|
| DC voltage measurement: | 200 mV \pm (0.5% + 2) @ 0.1 mV , 2 V \pm (0.5% + 2) @ 1 mV , 20 V \pm (0.5% + 2) @ 10 mV , 200 V \pm (0.5% + 2) @ 100 mV , 600 V \pm (0.8% + 2) @ 1 V |
| AC voltage measurement: | 200 V \pm (1.2% + 3) @ 0.1 mV : 45 Hz ... 400 Hz , 600 V \pm (1.2% + 3) @ 1 mV : 45 Hz ... 400 Hz |
| DC current measurement: | 2000 μ A \pm (1% + 2) @ 1 μ A , 200 mA \pm (1% + 2) @ 0.1 mA , 10 A \pm (2% + 5) @ 0.01 A |
| AC current measurement: | — |
| Resistance measurement: | 200 Ω \pm (0.8% + 5) @ 0.1 Ω , 2 k Ω \pm (0.8% + 5) @ 1 Ω , 20 k Ω \pm (0.8% + 5) @ 10 Ω , 200 k Ω \pm (0.8% + 5) @ 100 Ω , 2 M Ω \pm (0.8% + 5) @ 1 k Ω , 20 M Ω \pm (1% + 5) @ 10 k Ω |
| Capacitance measurement: | — |
| Inductance measurement: | — |



DATA SHEET

| | |
|--|---|
| Frequency measurement: | - |
| Square-wave signal duty ratio measurement: | - |
| Temperature measurement: | - |
| Automatic change of measuring ranges: | - |
| hFE: | ✓ |
| Diode test: | ✓ |
| Sound signal of the continuity test: | ✓ |
| Checking TTL logic states: | - |
| RS-232: | - |
| Main features: | <ul style="list-style-type: none">• Measurement of the battery discharge level: 9V, 1.5V,• Hold - stopping the meter reading,• LCD display,• Aesthetic and solid construction,• Low battery level alarm |
| Power supply: | 9V, type 6F22 battery - included |
| Weight: | 0.2 kg |
| Dimensions: | 140 x 74 x 38 mm |
| Manufacturer / Brand: | UNI-T |
| Guarantee: | 2 years |