

Code: UT-620A

LOW RESISTANCE METER **UT-620A** UNI-T

The UT-620A meter allows you to measure low resistances (even a few mΩ). Due to the intended use of the device, the measurement should always be performed with the use of dedicated measurement probes attached to the product.



Resistance measurement:	120 mΩ ± (0.25% + 25) @ 0.01 mΩ , 600 mΩ ± (0.25% + 25) @ 0.01 mΩ , 6 Ω ± (0.25% + 25) @ 0.0001 Ω , 60 Ω ± (0.25% + 25) @ 0.001 Ω , 600 Ω ± (0.25% + 25) @ 0.01 Ω , 6 kΩ ± (0.75% + 30) @ 0.0001 kΩ
Automatic change of measuring ranges:	—
RS-232:	—
USB:	✓
Main features:	<ul style="list-style-type: none"> • Hold - stopping the meter reading, • 4-lead measurement, • Large, readable LCD display with backlight, • Low battery level alarm, • Aesthetic and solid construction, • The set includes a practical case
Power supply:	Built-in 7.4V / 4000mAh battery, 9V / 4A power adapter included
Weight:	1.33 kg
Dimensions:	269 x 182 x 60 mm
Manufacturer / Brand:	UNI-T



DATA SHEET

Guarantee:	2 years
------------	---------