

Code: IP-5-11-M2

## SWITCH POE **IP-5-11-M2** 5-PORT ATTE

The IP-5-11-M2 set consists of the XPOE-6-11-OF switch module and the APS-90-480-OF switching power supply enclosed in the ABOX-M2 external enclosure with IP56 tightness class.

The LONG RANGE operation mode allows to increase the range of power and data transmission for ports LAN 1 ... LAN 4 to 280m while limiting the network bandwidth for these ports to 10Mbps.



LAN ports:	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T - Uplink</li> <li>• 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE</li> </ul>
Management:	—
LED diodes:	Power, LAN
Transmission speed:	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports
Maximal output power:	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - 1 ... 4 ports,</li> <li>• 70 W @ Passive PoE - Port 5,</li> <li>• 30 W @ PoE (802.3af/at) - 1 ... 5 ports</li> </ul>
Maximal total power:	96 W
Operation modes:	<ul style="list-style-type: none"> <li>• Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports</li> <li>• Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5</li> <li>• Port LAN 6 - Uplink</li> </ul>



# DATA SHEET

Main features:	<ul style="list-style-type: none"><li>• Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port)</li><li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports</li><li>• The modular design streamlines service tasks and enables quick and easy system expansion</li><li>• The raster system of module assembly facilitates the expansion of the device by further modules</li><li>• The ABOX-M2 mounting enclosure is equipped with 7 cable entries with glands in the 6 x M16 + 1 x M20 arrangement</li></ul>
Power supply:	230 V AC - cable terminals
Weight:	0.65 kg
Dimensions:	226 x 148 x 80 mm
Manufacturer / Brand:	ATTE
Guarantee:	<b>3 years</b>