

Code: VF-6800P/COMBO

UNIVERSAL METER **VF-6800P/COMBO** DVB-T/T2 DVB-S/S2 DVB-C/C2 Spacetronik

The VF-6800P/COMBO allows to measure the TV signals at DVB-T/T2, DVB-S/S2, DVB-C/C2 installations. Readable menu will help the operation for any installer.



Output and input:	1 pcs F socket, 1 pcs IEC socket, 1 pcs mini USB, 1 pcs 2.1/5.5 mm socket
Display:	2.4 " TFT LCD
Frequency range:	• 42 MHz ... 1005 MHz - DVB-T / DVB-T2 / DVB-C / DVB-C2, • 950 MHz ... 2150 MHz - DVB-S / DVB-S2
Signal level:	-20 ... -80 dBm
LNB power supply:	13 / 18 V
Switching between bandwidths:	0 / 22 kHz
DiSEqC:	DiSEqC 1.0, 1.1, 1.2, USALS systems support
Antenna powering:	5 / 12 V
Video signal test:	—
Programming and firmware upgrade:	via micro USB port
Battery power supply:	• Li-Ion battery 7.4 V / 2000 mAh • 12 V / 1 A (power adapter included)

Main features:	• Measurement of signal strength and quality • Signal indicator : LED display / Beep signal • Measurement of BER, MER • Spectrum measurement mode • LNB overvoltage protection • LNB indicator and short-circuit protection • Support for a satellite dish motor • UNICABLE technology support • Signal lock audible notification • Clear graphical interface • OSD menu full in Polish • Car charger included in the kit • Long standby time • Low power consumption • Compass • Flashlight built-in • Illuminated buttons • Anti-shock silicone case
Weight:	0.3 kg
Dimensions:	170 x 93 x 42 mm
Supported languages:	Polish, English, Spanish, Portuguese, Russian
Manufacturer / Brand:	Spacetronek
Guarantee:	2 years