

Code: MT-22-L

MONITOR HDMI, VGA **MT-22-L** 21.5 " UNIARCH

Monitor is equipped with one analog VGA input and one digital HDMI input. The LED matrix illumination technology allows to real colors reproduction, 40% lower current consumption and much lower failure rate compared to normal LCD monitors with CCFL illumination.



Screen size:	21.5 "
Native resolution:	1920 x 1080 px
Aspect ratios:	16 : 9
Matrix type:	TFT LCD
Contrast:	4000 : 1
Brightness:	250 cd/m ²
Viewable angles:	178 ° horizontal 178 ° vertical
Response time:	6.5 ms
Speakers built-in:	—
Signal connectors:	<ul style="list-style-type: none"> • 1 x HDMI • 1 x VGA • 1 x Power socket
Number of displayed colors:	16.7 M



DATA SHEET

Refresh frequency:	60 Hz
HDCP:	✓
Housing type:	Plastic
DLNA:	—
Monitor mounting standard:	VESA 100
Robbery protection:	✓
Parameters adjustment:	OSD - by monitor control keys
Power supply:	12 V DC / 2 A (power adapter included)
Power consumption:	<ul style="list-style-type: none">• < 23 W (typical)• < 0.5 W (in standby mode)
Weight:	2.51 kg
Dimensions:	<ul style="list-style-type: none">• 508 x 394 x 210 mm (with stand)• 508 x 308 x 40 (without stand)
Manufacturer / Brand:	UNIVIEW / UNIARCH
Guarantee:	3 years

