

Code: STC-23

UNIVERSAL METER **STC-23** DVB-T/T2 DVB-S/S2 DVB-C Spacetronek

The STC-23 allows to measure the TV signals at DVB-T/T2, DVB-S/S2, DVB-C installations. Readable menu will help the operation for any installer.



| | |
|-----------------------------------|--|
| Output and input: | 1 pcs F socket, 1 pcs IEC socket, 1 pcs mini USB, 1 pcs 2.1/5.5 mm socket |
| Display: | 2.4 " TFT LCD |
| Frequency range: | <ul style="list-style-type: none"> • 42 MHz ... 1005 MHz - DVB-T / DVB-T2 / DVB-C, • 950 MHz ... 2150 MHz - DVB-S / DVB-S2 |
| Signal level: | -20 ... -80 dBm |
| LNB power supply: | 13 / 18 V |
| Switching between bandwidths: | 0 / 22 kHz |
| DiSEqC: | DiSEqC 1.0, 1.1, 1.2, USALS systems support |
| Antenna powering: | 5 / 12 V |
| Video signal test: | — |
| Programming and firmware upgrade: | via micro USB port |
| Battery power supply: | <ul style="list-style-type: none"> • Li-Ion battery 7.4 V / 2000 mAh • 12 V / 1 A (power adapter included) |



DATA SHEET

| | |
|-----------------------|--|
| Main features: | <ul style="list-style-type: none">• Measurement of signal strength and quality• Signal indicator : LED display / Beep signal• Measurement of BER, MER• Spectrum measurement mode• LNB overvoltage protection• LNB indicator and short-circuit protection• Support for a satellite dish motor• UNICABLE technology support• Signal lock audible notification• Clear graphical interface• OSD menu full in Polish• Car charger included in the kit• Long standby time• Low power consumption• Compass• Flashlight built-in• Illuminated buttons• Anti-shock silicone case |
| Weight: | 0.3 kg |
| Dimensions: | 170 x 93 x 42 mm |
| Supported languages: | Polish, English, Spanish, Portuguese, Russian, French |
| Manufacturer / Brand: | Spacetronek |
| Guarantee: | 2 years |