


## DATA SHEET

## Code: 12V/4A/GPV SWITCHING ADAPTER **12V/4A/GPV**



Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.

Please pay attention for proper cooling conditions of the power adaptor during work!



| Adapter type:          | Switching   |
|------------------------|---|
| Power voltage:         | 100 240 V AC  |
| Frequency range:       | 50 / 60 Hz  |
| Output voltage:        | 12 V DC   |
| Maximal load:          | 4 A   |
| Output power:          | 48 W  |
| Number of outputs:     | 1 pcs   |
| Protections:           | <ul> <li>Overload</li> <li>Short-circuit</li> <li>Overvoltage</li> <li>Temperature</li> </ul> |
| Housing type:          | Plastic   |
| Operation temp:        | -20 °C 70 °C  |
| "Index of Protection": | IP67  |
| Main features:         | Box casing designed to wall mounting  |
| Weight:                | 0.31 kg   |
| Dimensions:            | 148 x 40 x 34 mm  |
| Guarantee:             | 2 years   |



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

12V/4A/GPV