

Code: IPC-C26W-BAT

IP CAMERA **IPC-C26W-BAT** Wi-Fi - 1080p 2.8 mm

The wireless IP camera allows you to record events on a micro SD card after motion is detected by the built-in PIR detector. The device allows you to save data to the cloud and remotely access them. Built-in lithium battery Li-Ion enables operation for a period of 2-3 months in places where there is no possibility of connecting cables.

Camera is according to IP65 Index of Protection norm.



Standard:	TCP/IP
Sensor:	1/3 " CMOS - Hi 3518E V300
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	2.8 mm / F2.0
View angle:	<ul style="list-style-type: none"> • 110 ° (manufacturer data) • 105 ° (our tests result)
IR illuminator:	✓
Min. illumination:	0.01 Lux (color) 0.01 Lux (B/W)
RS-485 interface:	—
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
ONVIF:	—
Alarm inputs / outputs:	—

Audio:	<ul style="list-style-type: none"> • Microphone • Speaker • Bi-directional audio streaming support
Network interface:	2.4 ... 2.4835 GHz Wi-Fi : IEEE 802.11 b/g/n
Mobile phones support:	<ul style="list-style-type: none"> • Android: Free application VicoHome • iOS (iPhone): Free application VicoHome
Default IP address:	—
Default user password:	—
Web browser access ports:	—
PC client access ports:	—
Main features:	<ul style="list-style-type: none"> • The device supports the cloud, which is also possible to access from the smartphone using the application • Built-in PIR detector - Motion detection recording, • Receive alarm notifications in the application when the camera detects motion, • Alarm signaling via LED and/or siren (it is possible to manually start the alarm) • Video recording to micro SD card with playback possibility • IR illuminator • ICR - Movable InfraRed filter • Live image view • Software update via network • RESET button • The camera is equipped with a magnetic holder
Power supply:	<ul style="list-style-type: none"> • 2x Li-Ion, 21700 battery - 3.7 V, 4800 mAh • Charging via micro USB port - 5 V / 1 ... 2 A
Current consumption:	<ul style="list-style-type: none"> • 0.3 mA Standby • 250 / 510 mA Operation - Day/night mode
Backup time:	2 ... 3 months
Charging time (recover to 100% capacity):	8 ... 10 h
Housing:	Plastic
Color:	White + Black
"Index of Protection":	IP65
Vandal-proof:	—
Operation temp:	-20 °C ... 50 °C
Weight:	0.35 kg
Dimensions:	97 x 63 x 72 mm
Guarantee:	2 years