

Code: ATLO-KRMD-512

CODE LOCK **ATLO-KRMD-512**

Outdoor, autonomous code lock with RFID reader.
Autonomous operation of the device allows the user to:

- Open by using a card or PIN code.
- Remember stored cards or PIN codes.
- Signaling left the door open.
- Acoustic and optical signaling.

Administrator capabilities are following:

- Programming by using the keypad.
- Adding a new card by using the keypad.
- Adding a new card and entering a PIN code.
- Changing the PIN code of the user.
- Deleting the PIN code of the user.
- Setting the lock release time.
- Restoring the default settings.



Cards support:	Unique EM 125kHz
Reading distance of prox-keys:	max. 3 cm
Autonomous operation:	✓
Keyboard built-in:	✓
Doorbell button:	✓
Tamper output:	—
Communication:	Wiegand 26, Wiegand 34
Power supply:	<ul style="list-style-type: none"> • 12 V DC ± 10 % • 12 V AC ± 10 %
Maximal current consumption:	<ul style="list-style-type: none"> • 30 mA (Standby mode) • 60 mA (operation)
Relay contacts load:	3 A / 12 V

Main features:	<ul style="list-style-type: none"> • 2000 indexed users • Identification: Card and/or PIN • Blue backlight of the keys • Support for door contact and exit button • NO/NC output, • Wiegand interface 26 / 34 bit, • Ability to use codes without associated cards • Number of relay outputs : 1, • Electric strikes and electromagnetic locks support • Reversing bolt support • Possible connection of the external ATLO-R series reader (read in/out door control) • Blue backlight
Operation temp:	-40 °C ... 60 °C
Permissible relative humidity:	10 ... 90 % (non-condensing)
Housing:	Metal
Color:	Silver + Black
"Index of Protection":	IP68
Vandal-proof:	✓
Weight:	0.49 kg
Dimensions:	78 x 115 x 25 mm
Manufacturer / Brand:	ATLO
Guarantee:	3 years

