

Code: PFS4218-16ET-240-V2

SWITCH POE **PFS4218-16ET-240-V2** 16-PORT SFP DAHUA

Due to reliability and ensuring high quality of transmission, the PFS4218-16ET-240-V2 10/100 Mb/s 16-port PoE desktop type switch is perfect solution for expanding home or office network.

Attention! The SFP port requires the SFP module, which is available in our offer.



LAN ports:	<ul style="list-style-type: none"> • 16 x RJ45 - 10/100 Base-T (14 PoE (802.3af/at) + 2 Hi-PoE / port Hi-PoE / PoE 802.3bt / PoE (802.3af/at)) • 2 x Uplink (port SFP - 1000 Base-X / RJ45 - 10/100/1000 Base-T)
Management:	✓
Transmission speed:	<ul style="list-style-type: none"> • Ethernet - 10 Mbps Full Duplex • Fast Ethernet - 100 Mbps Full Duplex • Gigabit Ethernet - 1000 Mbps Full Duplex (Uplink)
Maximal output power:	<ul style="list-style-type: none"> • 30 W / port PoE • 90 W / port Hi-PoE / port Hi-PoE / PoE 802.3bt
Maximal total power:	240 W
MAC addresses table:	4k
Main features:	<ul style="list-style-type: none"> • Switch is web managed • Intelligent management of Power Supply Unit power's output stage protection against lightning discharges and voltage differences and strokes between devices • IEEE 802.1Q VLAN • PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • Ports marked in red support IEEE802.3af, IEEE802.3at, IEEE802.3bt and Hi-PoE standards with a maximum output power of 90 W per port - designed to power high power devices • Range PoE : 250 m • The device supports 8-pin power supply
LED diodes:	Power : 50 % / 80 % / 100 %, Link, PoE, System
Certificates:	CE
Power supply:	100 ... 240 V AC
Housing type:	RACK 19", 1U
Operation temp:	-10 °C ... 55 °C
Weight:	3.2 kg
Dimensions:	440 x 300 x 44 mm



DATA SHEET

Manufacturer / Brand:	DAHUA
Guarantee:	3 years

