

Code: MCT82M-IO

PROXIMITY READER WITH KEYPAD **MCT82M-IO** ROGER

Indoor proximity cards and key-fobs reader. 13.56 MHz S50 standard.

The readers with IO option offer the set of inputs and outputs which, in most cases, should be capable to operate single door passage without necessity to use inputs or outputs located on access controller or expansion unit.



Support:	RACS 5 (Roger)
Cards support:	13.56 MHz S50
Reading distance of prox-keys:	max. 7 cm
Keyboard built-in:	✓
Autonomous operation:	✓
Doorbell button:	—
Tamper output:	✓
Communication:	RS-485
Main features:	<ul style="list-style-type: none"> • Tamper protection (detection of removing from mounting surface and enclosure opening) • LED indication • Beep signal • Touch and backlit keyboard buttons • 3 Inputs, • Multifunctional parametric inputs including Double Wiring • 2 Transistor outputs, • 1 Relay output
Power supply:	10 ... 15 V DC



DATA SHEET

Average current consumption:	60 mA
Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	10 ... 95 % (non-condensing)
"Index of Protection":	IP41
Weight:	0.12 kg
Dimensions:	85 x 85 x 22 mm
Manufacturer / Brand:	ROGER
Guarantee:	3 years