

Code: ASA3213GL-MW

TIME & ATTENDANCE RECORDER **ASA3213GL-MW** DAHUA

Access controller with face recognition function.



Sensor:	CMOS
Matrix size:	2 Mpx
Resolution:	1920 x 1080 - 1080p

General information:

Standard:	TCP/IP
IR illuminator:	✓
LED illuminator:	✓
Temperature measurement:	—
Temperature measurement range:	—
Accuracy of temperature measurement:	—
Face recognition distance:	0.3 m ... 1.5 m (max 500 faces in the database)
RFID proximity reader built-in:	<ul style="list-style-type: none"> • 13.56 MHz S50 • Memory of 500 RFID cards
Internal memory:	Support storage of 150 000 records



DATA SHEET

Video output:	—
RS-485 interface:	✓
RS-232 interface:	—
Wiegand interface:	—
USB:	1 x USB 2.0
Memory card slot:	—
Alarm inputs / outputs:	1 / 1 - Relay outputs
Audio:	Voice message
Network interface:	1 x 10/100 Base-T (RJ-45)
Network protocols:	IPv4, RTSP, RTP, TCP, UDP, P2P
WEB Server:	Built-in
ONVIF:	—
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777
PC client access ports:	37777
Main features:	<ul style="list-style-type: none">• Built-in LCD display showing the image from the video camera - 4.3 " capacitive touch screen, 480 x 272 px• Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above• 500 users• Software update via network• Real-time Surveillance• Multiple Authentication• Take face image after swiping card• Auto-Registration• Recording of information about Time&Attendance• The possibility of programming group or individual work schedules, taking into account the permissible time of lateness and earlier exit• Statistical Reporting• Backup to USB drive (pendrive, external drive)• Output button support• Door status detection• Lock control• Tamper protections
Power supply:	12 V DC / 1.5 A (power adapter included)
Power consumption:	≤ 18 W
Housing:	Plastic (ABS)
Color:	Black + Silver
"Index of Protection":	—
Operation temp:	-10 °C ... 55 °C
Weight:	<ul style="list-style-type: none">• 0.22 kg (without stand)• 0.24 kg (with stand)



DATA SHEET

Dimensions:	<ul style="list-style-type: none">• 116 x 107 x 22 mm (without stand)• 116 x 107 x 78 mm (with stand)
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years