

Code: DS-2DE4225IW-DE(S6)

IP SPEED DOME CAMERA OUTDOOR **DS-2DE4225IW-DE(S6)** - 1080p 4.8 ... 120 mm Hikvision

IP camera equipped with very good high resolution sensor. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition.

Built-in IR illuminator allows to operate at night conditions, and vari-focal lens with wide range of view angle adjustment enables optimal set the view field of camera to all conditions. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3at standard makes the device more universal and easier to install.

For a few models of IP cameras working at $\geq 1920 \times 1080$ resolution we recommend to use of network with 1Gb/s bandwidth.



| | |
|---------------------------|---|
| Standard: | TCP/IP |
| Sensor: | 1/2.8 " Progressive Scan CMOS |
| Matrix size: | 2.1 Mpx |
| Resolution: | 1920 x 1080 - 1080p 1280 x 960 - 1,3 Mpx 1280 x 720 - 720p |
| Scanning system: | Progressive |
| Lens: | 4.8 ... 120 mm |
| View angle: | <ul style="list-style-type: none"> • 57 ° ... 2.5 ° (manufacturer data) • 53 ° ... 3.1 ° (our tests result) |
| Optical zoom: | x 25 |
| Digital zoom: | x 16 |
| Range of IR illumination: | 100 m |
| S/N ratio: | > 52 dB |



DATA SHEET

| | |
|----------------------------------|--|
| Video output: | — |
| Preset rotation speed: | 80 °/s |
| Rotation speed (manual control): | 0.1 °/s ... 80 °/s (horizontal) 0.1 °/s ... 80 °/s (vertical) |
| Horizontal rotation range: | 360 ° - continuous |
| Vertical rotation range: | -15 ° ... 90 ° |
| RS-485 interface: | — |
| Number of presets: | 300 |
| Horizontal scan: | ✓ |
| Route settings: | 8 |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| Bitrate: | 32 ... 16384 kbps |
| Alarm inputs / outputs: | 1 / 1 |
| Audio: | <ul style="list-style-type: none">• External microphone input• Audio output• Audio detection• Noise reduction |
| Main stream frame rate: | 1 ... 25 fps - 1080p |
| Network interface: | 10/100 Base-TX (RJ-45) |
| Network protocols: | IPv4/IPv6, HTTP, HTTPS, IEEE 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour, ISUP |
| WEB Server: | Built-in, NVR compliance |
| Max. number of on-line users: | 20 |
| ONVIF: | 18.12 |
| Memory card slot: | Micro SD memory cards up to 256GB support (possible local recording) |
| Mobile phones support: | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application Hik-Connect• iOS: Free application Hik-Connect |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Default IP address: | 192.168.1.64 |
| Web browser access ports: | 80 |
| PC client access ports: | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application |
| Mobile client access ports: | 8000 |
| Port ONVIF: | 80 |
| RTSP URL: | <ul style="list-style-type: none">• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ |



DATA SHEET

| | |
|------------------------|--|
| Main features: | <ul style="list-style-type: none">• WDR - 120 dB - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• ROI - improve the quality of selected parts of image• F-DNR (Defog) - Reduction of image noise caused by precipitation• BLC/HLC - Back Light / High Light Compensation• Intelligent 3D Positioning System• ICR - Movable InfraRed filter• Configurable Privacy Zones - 24• Motion Detection• Sharpness - sharper image outlines• Configurable: brightness, contrast, saturation• AGC - Automatic Gain Control• Day/Night mode (color/b&w/auto)• WB - White Balance (ATW/AWB/manual/indoor/outdoor)• Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its• Intelligent image analysis : crossing the line (tripwire), intrusion, abandoned/missing object, detection of entry into the area / exit from the area, face detection |
| Power supply: | <ul style="list-style-type: none">• PoE (802.3at),• 12 V DC / 2 A (power adapter included) |
| Power consumption: | ≤ 18 W |
| Housing: | Speed Dome, Metal + Plastic |
| Color: | White + Black |
| Operation temp: | -30 °C ... 65 °C |
| "Index of Protection": | IP66 |
| Weight: | <ul style="list-style-type: none">• 2.26 kg (without bracket)• 2.92 kg (with bracket) |
| Dimensions: | Ø 165 x 290 mm (without bracket) 245 x 165 x 240 mm (with bracket) |
| Supported languages: | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 327000146 |
| Guarantee: | 3 years |