

Code: DS-KV8413-WME1(B)/SU

## WIRELESS VIDEO DOORPHONE **DS-KV8413-WME1(B)/SU** Wi-Fi / IP Hikvision

Wi-Fi / IP video doorphone is dedicated to work with II generation IP Hikvision internal panels.

Video Doorphone is mounted in a surface housing.



Sensor:	2 Mpx
Resolution:	1920 x 1080
Camera view angle:	129 °
IR illuminator:	✓
LED illuminator:	—
PIR detector:	—
Doorbell button:	4 pcs
proximity reader built-in:	13.56 MHz S50
Wireless transmission range:	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard:	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n
Network interface:	<ul style="list-style-type: none"> <li>• Ethernet</li> <li>• Wi-Fi</li> </ul>
RS-485 interface:	✓
Video output:	—



# DATA SHEET

Video format:	H.264
Supported audio formats:	G.711
Alarm inputs:	4 pcs
Main features:	<ul style="list-style-type: none"><li>• WDR - 120 dB - Wide Dynamic Range</li><li>• DNR - Digital Noise Reduction</li><li>• BLC - Back Light Compensation</li><li>• Bidirectional communication,</li><li>• Full support via network : WiFi / LAN,</li><li>• Tamper detection - removing from mounting surface</li><li>• Video Doorphone is mounted in a surface housing</li><li>• IK rating : IK08</li></ul>
Power supply:	<ul style="list-style-type: none"><li>• PoE (802.3af)</li><li>• 12 V DC / 830 mA (max)</li></ul>
Power consumption:	< 10 W (operation)
Housing:	Aluminum + Plastic, Protects against weather conditions
Mount:	Surface-mounted
Color:	Black + Gray
"Index of Protection":	IP65
Operation temp:	-40 °C ... 53 °C
Weight:	0.38 kg
Dimensions:	174 x 91 x 29 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305302438
Guarantee:	<b>3 years</b>