

Code: GTX-B1-16-162SFP

SWITCH POE **GTX-B1-16-162SFP** 16-PORT SFP

Due to the reliability and ensuring high quality of transmission, the GTX-B1-16-162SFP 16-port PoE switch is an ideal solution for applications in CCTV IP installations. PoE powering possibility, compatible with the 802.3af/at standard makes the device more universal and easier to install.



LAN ports:	<ul style="list-style-type: none"> • 16 x RJ45 (16 x PoE (802.3af/at)), • 2 x Port SFP - Uplink
Management:	—
LED diodes:	Power, PoE, Link/Act, Speed
Transmission speed:	<ul style="list-style-type: none"> • 1000 Mbps : 2 x Port SFP - Uplink, • 10 / 100 / 1000 Mbps : 16 x Port LAN & PoE
Operation modes:	<ul style="list-style-type: none"> • NOM - Normal - the device operates as normal PoE switch • VLAN - 1 ... 14 ports • CENK (Surveillance Priority Transmission for Uplink) - port traffic balancing control to prevent loss of large data packets
Maximal output power:	30 W / port PoE - 1 ... 16 ports
Maximal total power:	300 W
MAC addresses table:	8k
Main features:	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • MTBF (Mean Time Between Faults) : 50000 h
Certificates:	CE, FCC Class B
Power supply:	100 ... 265 V AC
Operation temp:	-10 °C ... 45 °C
Weight:	3.17 kg
Dimensions:	440 x 290 x 45 mm, RACK 19", 1U
Guarantee:	2 years