

Code: ZS-0856

SET OF HEAT-SHRINKABLE QUICK-CONNECTORS WITH TIN AND TUBING **ZS-0856**

Heat-shrinkable quick-connector with tin is irreplaceable when we want to firmly and securely join or repair wires.

The heat-shrink tube has a ring with tin which, when heated to about 150°C, melts and joins the wires. In addition, there is an adhesive layer inside the quick-connector that strengthens and protects the connection against moisture. No additional insulation is required after the wires have been joined.



Number of pcs. in package:	<ul style="list-style-type: none"> • 5 pcs - white-transparent, • 20 pcs - red-transparent, • 20 pcs - blue-transparent, • 5 pcs - yellow-transparent
Wire cross-section range:	<ul style="list-style-type: none"> • 0.25 ... 0.35 mm² - white-transparent, • 0.5 ... 1.5 mm² - red-transparent, • 1.5 ... 2.5 mm² - blue-transparent, • 4.0 ... 6.0 mm² - yellow-transparent
Length:	<ul style="list-style-type: none"> • 27 mm - white-transparent • 40 mm - red-transparent • 40 mm - blue-transparent • 40 mm - yellow-transparent
The degree of shrinkage:	2:1
Shrinkage and tin melting temperature:	> 150 °C
Insulation:	Polyolefin
Maximal voltage:	600 V
Heat-shrink tube:	
Number of pcs. in package:	50 pcs - black
Length:	20 mm
The degree of shrinkage:	2:1
Diameter before shrink :	3.2 mm
Diameter after shrink :	1.6 mm
General information:	
Operation temp:	-55 °C ... 125 °C





DATA SHEET

Guarantee:	2 years
------------	---------