


DATA SHEET

Code: XVR5104HS-I3 AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **XVR5104HS-I3** 4 CHANNELS DAHUA

The XVR5104HS-I3 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.





Standard:	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs:	4 pcs BNC
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	1 pcs - CINCH 4 - Audio support via coaxial cable, HD-CVI only
Audio outputs:	1 pcs CINCH
Image compression method:	AI Coding / H.265+ / H.265 / H.264+ / H.264
Image records resolutions:	AHD / HD-CVI / HD-TVI : 5M-N - 1296 x 1440 , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , CVBS : 960H - 960 x 576 IP : max. 6 Mpx - 3072 x 2048
Recording speed adjustment:	6 Mpx IP @ 1 25 fps 5M-N @ 1 10 fps 4M-N @ 1 15 fps 1080p @ 1 15 fps 1080N @ 1 25 fps 720p @ 1 25 fps 960H @ 1 25 fps for each channel
Operation modes:	4 x AHD / HD-CVI / HD-TVI / CVBS / IP + 2 x IP



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

XVR5104HS-I3



DATA SHEET

Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 6 TB SATA
External storage devices backup:	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records:	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy) Intelligent face search AI - simultaneous search in the archive of face recordings based on max 8 photos taking into account the similarity threshold (for each photo separately) 1/4 channel synchronous playback
Network functions:	Full support via network, Remote records copying, Web Server built-in max. 128 on- line users
Mobile phones support:	 Port no.: 37777 or access by a cloud (P2P) Android: Free application <u>DMSS</u> iOS (iPhone): Free application <u>DMSS</u> See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Alarm inputs / outputs:	-
PTZ control:	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Main features:	 Cooperation with Dahua devices working in the concept of the Internet of Things (IoT), POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window, SMD PLUS - searching for an object classified as: human, motor vehicle Coax Audio/Alarm support, Intelligent image analysis : crossing the line (tripwire), intrusion, classification of people and vehicles advanced face recognition and search functions Support for up to 10 face databases, including 10 000 face images Detection of faces not included in the device database Searching for faces in recordings based on max 8 selected photos with the ability to independently set the similarity threshold for each photo
USB:	2 pcs USB 2.0
Mouse support:	✓
IR remote controller in the set:	-
Power supply:	12 V DC / 1.5 A (power adapter included)
Color:	Black
Weight:	0.87 kg
Dimensions:	260 x 236 x 48 mm
Supported languages:	Polish, English, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	DAHUA



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

XVR5104HS-I3



DATA SHEET

Guarantee:

3 years

