

Code: BCS-L-SNVR0801-4KE-8P

## NVR **BCS-L-SNVR0801-4KE-8P** 8 CHANNELS, 8 PoE



Standard:	TCP/IP
Supported resolutions:	max. 8.3 Mpx - 3840 x 2160 px 4K UHD
Video outputs:	1 pcs HDMI 4K 1 pcs VGA
Audio support:	8 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Supported hard drives:	1 x 10 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
Network protocols:	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, Alarm Server, IP Search, P2P, ONVIF
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function
Bitrate:	max. 80 Mbps
Network functions:	<ul style="list-style-type: none"> <li>• Web-Server built-in</li> <li>• CMS application</li> <li>• Live image view, Playback the records, Backup the records, remote access</li> </ul>
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	192.168.1.108



# DATA SHEET

Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
ONVIF:	✓
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">BCS Manager</a> • iOS (iPhone): Free application <a href="#">BCS Manager</a>
Alarm inputs / outputs:	—
PTZ control:	IP Speed Dome Cameras
USB:	2 pcs USB 2.0
Intelligent image analysis:	✓
Motion Detection:	✓
Main features:	Functions implemented in cooperation between the recorder and cameras that support these functions <ul style="list-style-type: none"><li>• crossing the line (tripwire)</li><li>• intrusion</li><li>• face detection</li><li>• SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle</li><li>• Privacy zones</li></ul>
Mouse support:	✓
IR remote controller in the set:	—
Operation temp:	-10 °C ... 50 °C
Switch PoE:	4-port PoE Switch built-in, 25.5 W / Channel
Maximum total switch load:	72 W
Power supply:	48 V DC / 1.81 A (power adapter included)
Weight:	0.7 kg
Dimensions:	270 x 205 x 15 mm
Supported languages:	English, Polish
Country of origin:	China
Manufacturer / Brand:	BCS Line
Guarantee:	<b>3 years</b>