

DATA SHEET

Code: TL-TAPO-P110

WI-FI SMART PLUG **TL-TAPO-P110** 3680 W TP-LINK

The TL-TAPO-P110 Wi-Fi Smart Plug allows to control the devices connected to it using the mobile application. For the proper management of the device, it is necessary to install the TP-Link Tapo mobile application. Remote access to the device requires connection to a Wi-Fi network with Internet access and is implemented with the use of the TP-Link cloud. Local access to the device and its control is also possible, even when the Internet is down. In this case, the smartphone or tablet with the Tapo application installed must be in the same Wi-Fi network as the controlled device.

Beyond direct control, the device has the ability to program the on and off schedule, and in "Away Mode" it can simulate the presence of household members by turning on and off connected devices at different times. The device has the ability to monitor real-time power consumption and energy spend via the Tapo app. Voice control allows you to control the device via voice commands from Amazon Alexa or the Google Assistant (Internet access required).



Rated voltage:	100 240 V, 50 / 60 Hz
Maximal total load:	3680 W
Total maximal current:	16 A
Number of outlets:	1 pcs
Socket type:	CEE 7/5
Plug type:	CEE 7/7
Grounding:	→
Wireless:	WiFi, 2.4000 - 2.4835 GHz
Mobile phones support:	• TP-Link Tapo (ANDROID) • TP-Link Tapo (iOS)



DATA SHEET

Main features:	• schedule, • timer, • remote access, • local access, • Away Mode – automatically turns devices on and off at different times to give the appearance that someone is home • Energy monitoring • Group control • Easy operation • IEEE 802.11 b/g/n • Supported data rates : 72 Mbps • Transmitter power max. 20 dBm • ON/OFF button • STATUS indicator • System requirements : Android 4.4 or newer, iOS 9.0 or newer
Housing:	Plastic PC
Color:	White
O	
Operation temp:	0 °C 40 °C
Permissible relative humidity:	0 °C 40 °C 10 % 90 % (non-condensing)
Permissible relative humidity:	10 % 90 % (non-condensing)
Permissible relative humidity: Weight:	10 % 90 % (non-condensing) 0.1 kg