

Code: APTI-W22C1S-TUYA

IP CAMERA **APTI-W22C1S-TUYA** Tuya Smart Wi-Fi - 1080p 3.6 mm

The cameras cooperating with the user-friendly Tuya platform have been designed with special care to simplify the configuration process and enable the user to create a simple and effective monitoring system.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The used Wi-Fi module allows to remote communication with camera for max. distance up to 30 m.

Attention! Devices cooperating with the Tuya platform do not have a WEB interface. The camera works only with the mobile application (the camera does not work with recorders). Controlling the device and schedule settings is possible if the device has access to the Internet.



Standard:	TCP/IP
Sensor:	Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	3.6 mm
View angle:	78 °
Range of IR illumination:	15 m
White light LED illuminator range:	—
Audio:	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Audio transmission via network, • Bi-directional audio streaming support
Image compression method:	H.264
Main stream frame rate:	<ul style="list-style-type: none"> • 15 fps @ 1080p • 25 fps @ 640 x 360 px
Network protocols:	TCP/IP
Network interface:	Wi-Fi - IEEE 802.11 b/g/n
ONVIF:	—
WEB Server:	—
Mobile phones support:	Access by a cloud (P2P) <ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS

Default IP address:	DHCP
Web browser access ports:	—
PC client access ports:	—
Mobile client access ports:	—
Port ONVIF:	—
RTSP URL:	—
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Main features:	<ul style="list-style-type: none"> • Wi-Fi module - IEEE 802.11 b/g/n, Range : 30 m (open area) • WDR - Wide Dynamic Range • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Motion Detection - Built-in PIR detector • Operation status LED indicator • RESET button
Battery operation time:	max. 90 days
Charging time (recover to 100% capacity):	6 h from USB port
Power supply:	<ul style="list-style-type: none"> • 4 x Li-Ion battery ICR18650 - 3.7 V / 2600 mAh (included), • Solar Panel : 7 W, • 5 V DC - micro USB socket (power adapter not included)
Housing:	Metal
"Index of Protection":	IP67
Weight:	<ul style="list-style-type: none"> • Camera : 0.77 kg (without bracket) 0.91 kg (with bracket)
Dimensions:	<ul style="list-style-type: none"> • 200 x 96 x 67 mm • 305 x 96 x 125 mm (with bracket)
Operation temp:	-30 °C ... 60 °C
Supported languages:	English
Manufacturer / Brand:	APTI
Guarantee:	2 years