

Code: IPC-HUM4231S-L4-0280B-S3

IP CAMERA **IPC-HUM4231S-L4-0280B-S3** PINHOLE - 1080p 2.8 mm DAHUA



Indoor micro camera equipped with very good quality CMOS sensor.

Camera is equipped with PINHOLE type lens, needs only a very small hole to get right field of view. Camera has microphone and audio output built-in.

Standard:	TCP/IP
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens:	2.8 mm (pinhole)
View angle:	<ul style="list-style-type: none"> • 96 ° (manufacturer data) • 92 ° (our tests result)
Min. illumination:	<ul style="list-style-type: none"> • 0.01 Lux @ F2.0 / 30IRE (color) • 0.001 Lux @ F2.0 / 30IRE (B/W)
S/N ratio:	> 56 dB
Audio:	<ul style="list-style-type: none"> • Audio input • Microphone built-in, • Audio output • Bi-directional audio streaming support • Audio detection



DATA SHEET

RS-485 interface:	—
RS-232 interface:	—
Alarm inputs / outputs:	—
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Main stream frame rate:	25 fps @ 1080p
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour
ONVIF:	21.06
WEB Server:	✓
Max. number of on-line users:	20
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	192.168.1.108
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Memory card slot:	—
Main features:	<ul style="list-style-type: none">• WDR - 120 dB - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• ROI - improve the quality of selected parts of image• BLC - Back Light Compensation• HLC - High Light Compensation (spot)• Configurable Privacy Zones• Motion Detection• Mirror - Mirror image• WB - White Balance (ATW/AWB/manual/indoor/outdoor)• AGC - Automatic Gain Control• IVS analysis - crossing the line (tripwire), intrusion, scene changing, Audio detection
Housing:	Mini - Metal
Color:	Black
Power supply:	12 V DC / 130 mA
Power consumption:	max. 1.56 W
Operation temp:	-40 °C ... 60 °C



DATA SHEET

Weight:	0.08 kg
Dimensions:	<ul style="list-style-type: none">• 44 x 35 x 30 mm• 50 cm (cable length)
Supported languages:	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian
Manufacturer / Brand:	DAHUA
Guarantee:	5 years