

Code: VTO2101E-P-S2

VIDEO DOORPHONE **VTO2101E-P-S2** DAHUA



The device cooperates with video doorphones, and other panels working in DAHUA IP / SIP standard.

The doorphone requires a SIP server, but it can be a SIP server for itself. After setting up the SIP server, the P2P option is available in the www panel. The use of a special firmware version in the VTH monitors is required.

ATTENTION! The device does not support the Dahua analogue system.

Compatibility:	DAHUA
Sensor:	1/2.8 ", 2.1 Mpx CMOS
Lens:	3.6 mm
View angle:	80 °
Image compression method:	H.265 / H.264
LED illuminator:	—
IR illuminator:	✓

Main features:	<ul style="list-style-type: none"> • It can only work with the mobile application, without the VTH monitor • The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH1 / VTH2 / VTH5 indoor panel • Doorbell button, • Lock control, • Bidirectional communication, • Microphone built-in, • Speaker built-in, • Noise and echo reduction • Tamper detection - removing from mounting surface • RS-485 interface • Alarm inputs - 1 pcs • Video PUSH personal messaging • Voice message • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • Day/Night mode (color/b&w/auto) • ICR - Movable InfraRed filter
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Power supply:	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 1 A, - DAHUA
Power consumption:	≤ 5 W (operation) ≤ 2.5 W (Standby mode)
Supported languages:	English
Housing:	Metal - Zinc alloy, Waterproof - IK10
Color:	Graphite
"Index of Protection":	IP65
Operation temp:	-40 °C ... 60 °C
Weight:	0.67 kg
Dimensions:	73 x 163 x 55 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years