

Code: APTI-501C2L-28WP

## IP CAMERA **APTI-501C2L-28WP** Full-Color - 5 Mpx 2.8 mm

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 5 MPx.

Camera bracket allows to adjust the camera to any direction, and power cables are hidden inside the bracket. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



|                                    |                                                                                                                    |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Standard:                          | IP                                                                                                                 |
| Sensor:                            | 1/2.8 " SONY Starvis™ Back-illuminated CMOS                                                                        |
| Resolution:                        | 2592 x 1944 - 5 Mpx ,<br>2560 x 1440 - 3.7 Mpx ,<br>1920 x 1080 - 1080p ,<br>1280 x 720 - 720p                     |
| Lens:                              | 2.8 mm                                                                                                             |
| View angle:                        | 93 °                                                                                                               |
| White light LED illuminator range: | 30 m                                                                                                               |
| Image compression method:          | H.265+ / H.265 / H.264+ / H.264 / MJPEG                                                                            |
| Main stream frame rate:            | 25 fps @ 5 Mpx                                                                                                     |
| Network interface:                 | 10/100 Base-T (RJ-45)                                                                                              |
| Memory card slot:                  | —                                                                                                                  |
| Alarm inputs / outputs:            | —                                                                                                                  |
| Audio:                             | <ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio transmission via network</li> </ul> |
| WEB Server:                        | Built-in                                                                                                           |



# DATA SHEET

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Max. number of on-line users:  | 10                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| ONVIF:                         | 19.12                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| RS-485 interface:              | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Mobile phones support:         | Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">BitVision</a></li><li>• iOS (iPhone): Free application <a href="#">BitVision</a></li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Default IP address:            | 192.168.1.168                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Default admin user / password: | admin / admin                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Web browser access ports:      | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| PC client access ports:        | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Mobile client access ports:    | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Port ONVIF:                    | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| RTSP URL:                      | rtsp://user:password@ip_address:80/0 - Main stream<br>rtsp://user:password@ip_address:80/1 - Sub stream                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Intelligent image analysis:    | <ul style="list-style-type: none"><li>• intrusion</li><li>• crossing the line (tripwire)</li><li>• loitering detection</li><li>• detection of people gathering</li><li>• vehicle detection</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Main features:                 | <ul style="list-style-type: none"><li>• WDR - 120 dB - Wide Dynamic Range</li><li>• 3D-DNR - Digital Noise Reduction</li><li>• ROI - improve the quality of selected parts of image</li><li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li><li>• Flicker Control - The technology eliminates the tiring eyes flickering image effect</li><li>• BLC/HLC - Back Light / High Light Compensation</li><li>• Motion Detection</li><li>• Privacy zones</li><li>• Possibility to change the resolution, quality and bit rate</li><li>• Mirror - Mirror image</li><li>• Sharpness - sharper image outlines</li></ul> |
| Power supply:                  | <ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC / 290 mA</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Power consumption:             | ≤ 3.5 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Housing:                       | Compact - Metal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Color:                         | White                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| "Index of Protection":         | IP67                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Operation temp:                | -20 °C ... 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Weight:                        | 0.45 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Dimensions:                    | 171 x 73 x 73 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Supported languages:           | Polish, English, Bulgarian Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Manufacturer / Brand:          | APT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Guarantee:                     | 2 years                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |