

Code: DS-3E1326P-EI(V2)

SWITCH POE **DS-3E1326P-EI(V2)** 24-PORT SFP Hikvision

The DS-3E1326P-EI(V2) switch is designed for large streams of video data in the CCTV IP surveillance networks.

Attention! The SFP port requires the SFP module, which is available in our offer.



LAN ports:	<ul style="list-style-type: none"> • 2 x port Combo: SFP (Base-X) / RJ45 (Base-T) • 24 x RJ45 10/100 Base-T (24 x PoE (802.3af/at))
Transmission speed:	<ul style="list-style-type: none"> • 10 / 100 Mbps - 24 LAN & PoE ports • 10 / 100 / 1000 Mbps - 2 Uplink ports • 1000 Mbps - 2 SFP ports
Maximal output power:	30 W / port PoE
Maximal total power:	370 W
MAC addresses table:	16k
Management:	✓
Default IP address:	192.168.1.64
Default admin user / password:	admin / -
Operation modes:	<ul style="list-style-type: none"> • Extend On : 300 m, 10 Mbps @ UTP cat. 5e, 6 • Extend Off : 100 m, 100 Mbps @ UTP cat. 5e, 6
Main features:	<ul style="list-style-type: none"> • 6 kV protection against lightning discharges and voltage differences and strokes between devices • High priority ports : 1 ... 8 • Configuration and management from the iVMS-4200 application • View topology and network status • Data Flow Control • Possibility of aggregation of G1, G2 ports • Statistical Reporting • Remote configuration • Remote update of software
LED diodes:	Power, Link/Act, PoE, PoE Max, G1, G2
Certificates:	CE
Power supply:	100 ... 240 V AC
Operation temp:	-10 °C ... 55 °C



DATA SHEET

Weight:	2.74 kg
Dimensions:	440 x 221 x 44 mm
Manufacturer / Brand:	Hikvision
SAP Code:	301802305
Guarantee:	3 years