

Code: 24V/1.5A/GPV

## SWITCHING ADAPTER **24V/1.5A/GPV**

Hermetic power supply in a plastic housing.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.

Please pay attention for proper cooling conditions of the power adaptor during work!



|                           |                                                                                                                           |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Adapter type:             | Switching                                                                                                                 |
| Power voltage:            | 90 ... 264 V AC                                                                                                           |
| Frequency range:          | 47 ... 63 Hz                                                                                                              |
| Output voltage:           | 24 V DC                                                                                                                   |
| Output voltage tolerance: | ± 3 %                                                                                                                     |
| Maximal load:             | 1.5 A                                                                                                                     |
| Output power:             | 36 W                                                                                                                      |
| Efficiency:               | 84 %                                                                                                                      |
| Number of outputs:        | 1 pcs                                                                                                                     |
| Protections:              | <ul style="list-style-type: none"> <li>• Overload</li> <li>• Short-circuit</li> <li>• Overvoltage</li> </ul>              |
| Main features:            | <ul style="list-style-type: none"> <li>• Protection class : II</li> <li>• Box casing designed to wall mounting</li> </ul> |
| Housing type:             | Plastic, Waterproof                                                                                                       |
| "Index of Protection":    | IP67                                                                                                                      |
| Operation temp:           | -20 °C ... 70 °C                                                                                                          |
| Weight:                   | 0.22 kg                                                                                                                   |
| Dimensions:               | 148 x 32 x 28 mm                                                                                                          |
| Guarantee:                | <b>3 years</b>                                                                                                            |