

Code: 24V/4.2A/GPV-MINI

## SWITCHING ADAPTER **24V/4.2A/GPV-MINI**

Hermetic power supply in a plastic housing.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.

Please pay attention for proper cooling conditions of the power adaptor during work!



Adapter type:	Switching
Power voltage:	190 ... 264 V AC
Frequency range:	50 / 60 Hz
Output voltage:	24 V DC
Output voltage tolerance:	± 5 %
Maximal load:	4.2 A
Output power:	100.8 W
Efficiency:	90 %
Number of outputs:	1 pcs
Protections:	<ul style="list-style-type: none"> <li>• Overload</li> <li>• Short-circuit</li> <li>• Overvoltage</li> <li>• Overheat</li> </ul>
Main features:	<ul style="list-style-type: none"> <li>• Protection class : II</li> <li>• Box casing designed to wall mounting</li> </ul>
Housing type:	Plastic, Waterproof
"Index of Protection":	IP67
Operation temp:	-20 °C ... 70 °C
Weight:	0.39 kg
Dimensions:	162 x 42 x 34 mm



# DATA SHEET

---

Guarantee:	3 years
------------	---------